

TR90B BATTERY POWERED

ELECTRONIC DESIGN	Computer controlled, high frequency converter
X-RAY OUTPUT	20 mA@40-60 kVDC, 15 mA@62-80 kVDC, 10 mA @82-90 kVDC, +15mA@82-90 kVDC in High Power Mode
INPUT POWER	Rechargeable lithium ion battery
BATTERY TYPE	60 VDC
TIMER	0.01-1.00 (+0.0130) 0.01 sec steps
INTERNAL POWER SUPPLY	Pulse Frequency Modulation High Frequency Inverter System
X-RAY TUBE	Toshiba D-0814
FOCAL SPOT SIZE	0.8 mm
ANODE HEAT STORAGE	9.86 kHU (7kJ)
COLLIMATOR	Mikasa Model R-300V, continuously adjustable light beam type with adjustable dual integrated laser pointers to indicate central ray and distance in bright ambient light conditions
LP4 LASER POINTERS	Class Illa; laser diode; max. output less than 3.0 mW, wavelength 635 mm
EXPOSURE SWITCH	Two stage deadman type with RJ11 connector
EXPOSURE CORD	8 ft (2.4 m)
SIZE	7.48 x 6.89 x 9.84 in (18.0 x 17.5 x 25.0 cm)
WEIGHT	15.0 lb (6.8 kg)
DR INTERFACE	RJ45 connector
BATTERY CHARGER	85-264V (AC, 50 Hz/60Hz)
BATTERY CHARGE	Constant Current: 2000 mA +/- 10%



Ordering Information

TR90B Tough Ray Battery Powered High Frequency Portable X-ray Unit

TR90B Tough Ray Battery Powered x-ray unit 20-10mA @ 40-90 kVDC with lightbeam collimator and integrated adjustable dual laser pointers, exposure switch and cord, two lithium ion batteries with AC charger and protective carrying case.

X200S

Tripod stand

X200SCC

Carrying bag for X200S tripod

TR90-RB

Replacement battery for TR90B

For more information about MinXray products, contact your local dealer or MinXray at:

MinXray, Inc. 3611 Commercial Avenue Northbrook, Illinois 60062 USA 1-847-564-0323

METHOD

Toll Free: 1-800-221-2245 (U.S. & CA.)
E-mail: info@minxray.com
www.minxray.com

Constant Voltage: 16.8V +/- 200mV



